

GRAFFITI REMOVER TOWELS™

TWL-200/220

Product Description

GR-TWL utilizes the SEI Migratory Technology that penetrates and chemically fractures the molecular bonds in paints, lacquers, enamels and stains. TWL-200's active ingredient migrates into and penetrates paints, coatings or unwanted marks and creates molecular space between the vandalism and the substrate, making the removal easy. The formula was designed for maximum consumer safety and therefore does not contain Methylene Chloride, chlorinated solvents, Methanol, Toluene, Xylene, Acetone, etc. The removal time varies from a few seconds to two minutes, depending on the type of coating and number of coatings to be removed.

TWL-200 is formulated by impregnating SEI Migratory Technology molecules into a unique and biodegradable towelette. Aside from being a high-end graffiti removal product, TWL-200 has a unique capability in that it will prevent corrosion on all metal surfaces after paint removal.

TWL-200's are also used for multi-purpose cleaning. They are effective on different types of paints, lacquers, enamels, waxes, dirt, grit, grease, adhesives, etc.

Chief Advantages

- Low odor
- Non-Toxic
- Biodegradable
- Works on all non-porous surfaces
- Safe to use on delicate surfaces

Packaging

- TWL-200 Container contains 25 wipes
- TWL-220 Container contains 45 wipes

Method of Application:

TWL-200 can be used on any surface and are pulled from the container and used directly on any unwanted vandalism or any area that needs to be cleaned. Simply blot the graffiti to be removed and then wipe away.

Product application must not be initiated during inclement weather or when precipitation appears to be imminent. Product must not be applied to wet, frozen or dirty surfaces. Always apply test area before proceeding with entire application. Application and removal can only be carried out by trained and certified SEI personnel and with care in order to maintain the coating's integrity, performance, longevity and warranty.

Please consult your SEI **Area Developer** for application, graffiti removal, specification and design and warranty assistance.

WARRANTY & DISCLAIMER

The information provided is to be used as a guide and customers should perform their own tests to ensure performance in their application. All data, statements, and recommendations made herein are based upon information we believe to be reliable, but are made without any representation, guarantee or warranty of accuracy. All statements, technical information and recommendations contained herein are based on tests SEI believes to be reliable, but the accuracy or completeness thereof is not guaranteed. SEI warrants its products will be free from defects when shipped to customer and should work in a manner consistent with its product data sheets should the products be applied in a commercially acceptable manner as determined by SEI. SEI under obligation of this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify SEI of the claimed defect within three months after the released invoice of product to customer. All freight charges for replacement products shall be paid by customer. SEI shall have no liability for any applications before or reapplication, injury, loss or damage arising out of the use of or the inability to use the products. Before using, user shall determine the suitability of the product for the intended use and carry out an appropriate test of the product and document such testing and assumes all risk and liability whatsoever in connection. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of SEI. The foregoing warranty is exclusive and in lieu of all other warranties expressed or implied. In no case shall SEI be liable for incidental or consequential damages. Limited warranty for industrial or commercial use. Keep out of reach of children, keep container sealed, Not for internal consumption. Consult material safety data sheet before use.